


AA

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets

(11)



EP 1 184 541 A1

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
06.03.2002 Bulletin 2002/10

(21) Application number: 01127006.3


(22) Date of filing: 20.09.1996

(51) Int Cl.7: F01K 23/10, F02C 7/16

<p>(84) Designated Contracting States: DE GB SE</p> <p>(30) Priority: 22.09.1995 JP 24475095 22.09.1995 JP 24475195</p> <p>(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC: 96306868.9 / 0 764 767</p> <p>(71) Applicant: Kabushiki Kaisha Toshiba Tokyo 105-8001 (JP)</p> <p>(72) Inventors: <ul style="list-style-type: none"> Ohtomo, Fumio 1-1 Shibaura 1-chome Minato-ku Tokyo 105 (JP) Nakata, Yuji 1-1 Shibaura 1-chome Minato-ku Tokyo 105 (JP) Fukuyama, Yoshitaka 1-1 Shibaura 1-chome Minato-ku Tokyo 105 (JP) </p>	<ul style="list-style-type: none"> Inomata, Asako 1-1 Shibaura 1-chome Minato-ku Tokyo 105 (JP) Shibuya, Sachio 1-1 Shibaura 1-chome Minato-ku Tokyo 105 (JP) Koga, Akinori 1-1 Shibaura 1-chome Minato-ku Tokyo 105 (JP) Ishii, Junji 1-1 Shibaura 1-chome Minato-ku Tokyo 105 (JP) Ito, Shoko 1-1 Shibaura 1-chome Minato-ku Tokyo 105 (JP) Yamamoto, Hironobu 1-1 Shibaura 1-chome Minato-ku Tokyo 105 (JP) <p>(74) Representative: Midgley, Jonathan Lee Marks & Clerk 57-60 Lincoln's Inn Fields GB-London WC2A 3LS (GB)</p> <p>Remarks: This application was filed on 14 - 11 - 2001 as a divisional application to the application mentioned under INID code 62.</p>
---	---

(54) **Combined cycle power plant**

(57) A combined cycle power plant comprises a gas turbine system (41) and a steam cycle system (42) having a steam turbine (118) to be driven by the steam generated by the waste heat of the exhaust gas of the gas turbine system (41), wherein the steam from the steam cycle system (42) flows through a gas turbine cooling system (43) of the gas turbine system to cool the gas turbine blades and other elements of the gas turbine system to be cooled and the waste heat of the gas turbine cooling system is effectively collected. The gas turbine cooling system (43) has cooling ducts (150, 160) formed in two or more than two elements (114, 149) of the gas turbine system to be cooled such as the gas turbine blades (149) and the combustor (114) of the gas turbine system so that steam is made to flow through the cooling ducts (150, 160) of these two or more than two elements (114, 149) to be cooled to effectively and maximally exploit the cooling potential and the waste heat collecting potential of the steam and hence improve the overall thermal efficiency of the plant. The plant can selectively supply steam and/or water from the steam cycle system or high pressure air from the gas turbine system.



EP 1 184 541 A1

Description

[0001] This invention relates to a combined cycle power plant realized by consolidating a gas turbine system and a steam cycle system, each being provided with one or more than one turbines.

[0002] More specifically, the present invention relates to a combined cycle power plant designed to improve the overall thermal efficiency of the plant by collecting the waste heat of the gas turbine system in said steam cycle system and enhancing the efficiency of collecting the waste heat of said gas turbine system.

[0003] There are known combined cycle power plants comprising a gas turbine system and a steam cycle system, wherein the steam cycle system is bled of steam and the bled steam is used as a cooling medium for cooling the turbine blades of the gas turbine while the heat collected by the cooling operation is returned to the steam cycle system to improve the overall thermal efficiency of the plant.

[0004] Combined power plants of the above identified type are advantageous in that the turbine inlet gas temperature can be raised to improve the thermal efficiency of the turbine as a result of the cooling operation using steam as a cooling medium and, at the same time, the waste heat of the gas turbine system is partly collected and returned to the steam cycle system to improve the overall thermal efficiency of the plant.

[0005] FIG. 1 of the accompanying drawings schematically illustrates a known combined cycle power plant comprising a gas turbine system 1 and a steam cycle system 2 having a steam turbine driven by the waste heat of the gas turbine system 1.

[0006] The gas turbine system 1 by turn comprises a gas turbine 11, a compressor 13 coupled with the gas turbine 11 by means of a shaft 12 and a combustor 14 that receives compressed air and fuel from the compressor 13 and burns the fuel to produce hot high pressure gas for driving the gas turbine 11.

[0007] The compressor 13 compresses the ambient air fed in through an air duct 15 and the compressed air is partly used for cooling the blades and sealing the rotary components of the gas turbine 11, while the remaining compressed air is fed to the combustor 14.

[0008] The combustor 14 burns the fuel fed from a fuel supply system (not shown), using the compressed air as combustion sustaining gas. The hot gas obtained by combustion is then fed to the gas turbine 11 by way of a combustion gas duct 16 and allowed to inflate to drive the gas turbine 11 before flowing out through an exhaust gas duct 17.

[0009] On the other hand, the steam cycle system 2 comprises a steam turbine 18 and an electric generator 20 coupled with the steam turbine 18 by means of a shaft 19. A steam cycle is established in the steam cycle system as it generates steam by the waste heat of the gas turbine system 1 and the generated steam is used to drive the steam turbine 18. Note that the rotor of the

steam turbine 18 and that of the gas turbine 11 are linked by a shaft 22 in FIG. 1.

[0010] The steam cycle system 2 is additionally provided with a waste heat collector boiler 23 for collecting heat from the exhaust of the gas turbine 11 fed through the exhaust gas duct 17 and generating hot high pressure steam necessary for driving the steam turbine 18. The exhaust gas from the waste heat collector boiler 23 is then emitted into the atmosphere by way of a flue 27.

[0011] A high pressure superheater 24, a high pressure evaporator 25 and a high pressure preheater 26 are arranged in the waste heat collector boiler 23 in the above mentioned order from the upstream side toward the downstream side thereof. These heaters and the steam turbine 18 are connected with each other in a manner as described below to establish a steam cycle 2.

[0012] The steam expelled from the steam turbine 18 is led to a steam condenser 29 by way of an expelled steam duct 28 and reduced to water at room temperature. The collected room temperature water is led to the high pressure preheater 26 by way of a circulation pump 30 and a circulation conduit 31 for preliminary heating and then to a high pressure drum 33 by way of a conduit 32 leading to the drum.

[0013] The pressurized water in the high pressure drum 33 is led to the high pressure evaporator 25 by way of a pressurized water circulation pump 34 and a pressurized water circulation conduit 35 for evaporation and the produced hot high pressure steam is returned to an upper space of the high pressure drum 33 by way of a return duct 36. The returned steam is then fed to the high pressure superheater 24 by way of a steam duct 37 for reheating and the heated steam is further fed to the steam turbine 18 by way of a steam supply duct 38.

[0014] In a combined cycle power plant having a configuration as described above, the inlet gas temperature of the gas turbine 11 is preferably made as high as possible in order to enhance the thermal efficiency of the plant. On the other hand, the combustor 14 and the stator vanes and the rotor blades of the gas turbine 11 have to be made of a highly heat-resistant material to achieve a high inlet gas temperature for the gas turbine 11.

[0015] The upper temperature limit of currently available heat-resistant super alloys that can be used for gas turbines is about 800 to 900°C. On the other hand, the inlet gas temperature of newly constructed gas turbines is typically as high as about 1,300°C, a level far exceeding the upper temperature limit of heat-resistance super alloys. Therefore, the temperature of the blades of the turbine 11 has to be lowered by some means to the upper temperature limit of the heat-resistant super alloy of which they are made. In the case of gas turbines having an inlet gas temperature of about 1,300°C, the blades are typically cooled by part of the air expelled from the compressor 13.

[0016] However, Air-cooling systems using air as cooling medium intrinsically show a rather poor effect. Therefore, cooling air has to be made to flow at a re-

markedly high rate to cool the blades of the turbine if the inlet gas temperature rises above 1,300°C.

Further more, the convection cooling inside the blades alone cannot achieve a sufficient cooling effect and a film cooling technique of blowing out cooling air through pores arranged on the surface of the effective area of each blade has to be used as supplementary means.

[0017] The use of a film cooling technique is accompanied by a problem of reduced temperature of main stream gas as the blown out cooling air and the main stream gas are mixed with each other. This means that the combustor 14 has to be designed so as to withstand a higher outlet temperature and, at the same time, suppress the emission of NOx gas at such high temperature. If these design requirements are met, the combustor 14 consumes air and fuel at an enhanced rate.

[0018] As discussed above, the gas turbine having an air cooling system of a combined cycle power plant is inevitably accompanied by the problem of reduced thermal efficiency, which by turn reduces the overall thermal efficiency of the plant. Additionally, the pores on the surface of the blades can become clogged when low quality fuel containing impurities is used so that the plant has to be sensitive about the fuel it consumes in order to avoid the use of low quality fuel.

[0019] Japanese Patent Publication No. 63-40244 and Japanese Patent Application Laid-Open No. 4-124414 disclose techniques of using steam whose specific heat is twice as large as that of air as cooling medium in a gas turbine in order to bypass the above identified problems. With any of the proposed techniques, part of the steam to be used for the steam turbine of a combined cycle power plant is made to flow through the cooling duct arranged in the blades of the gas turbine to cool the blades and, after cooling the blades, put back to the remaining steam that is being fed to the steam turbine.

[0020] A combined cycle power plant realized by applying such a technique consumes steam at a rate far below the air consumption rate of a comparable plant that does not use the technique and achieves a desirable cooling effect without blowing out steam through the blades of the gas turbine. The steam used for cooling the blades is collected and roused to drive the steam turbine. Thus, the use of such a technique can effectively prevent any significant temperature fall in the main stream gas and a rise in the consumption rate of fuel and air within the combustor to improve the overall thermal efficiency of the plant. Additionally, the gas turbine can be adapted to low quality fuel.

[0021] However, in any known combined cycle power plants designed to cool the blades of the gas turbine with steam by allowing part of the steam for the steam turbine to flow through the cooling duct arranged in the gas turbine blades and thereafter to be combined with the remaining steam, the two parts of steam are actually put together at the inlet of the steam turbine before fed to it so that it is rather difficult to accurately control the steam

flow rate, the steam pressure and the steam temperature to get to respective target values at the inlet of the steam turbine and achieve a maximum thermal efficiency for the plant.

[0022] Japanese Patent Application Laid-Open No. 6-93810 proposes a technique of dissolving this problem by returning substantially the entire steam that has passed through the cooling duct to the heating region of the steam cycle system.

[0023] While a combined cycle power plant realized by applying such a technique can control the steam flow rate, the steam pressure and the steam temperature to get to respective target values at the inlet of the steam turbine, the obtainable temperature rise of the steam collected after cooling the blades is 50 to 200°C at most and the steam still can be used for cooling, revealing that the effective use of heat in the plant is not maximized yet.

[0024] As discussed above, any known combined cycle power plants still have problems to be solved in terms of the effectiveness of cooling the gas turbine system and the efficiency of collecting waste heat from the gas turbine system. Therefore, there exists a demand for combined cycle power plants having an improved overall thermal efficiency achieved by solving the above identified problems.

[0025] In a combined cycle power plant of the type under consideration, scaly debris contained in the steam passing through the cooling duct of the turbine blades of the gas turbine system can be deposited in the duct to reduce the cooling efficiency of the steam and the efficiency of collecting waste heat of the plant. This problem of undesired deposits of scaly debris by turn imposes limitations to the profile and the cross section of the cooling duct of the turbine blades to suppress the attempt for improving the cooling efficiency and the efficiency of collecting waste heat.

[0026] In view of the above identified problems, it is therefore the object of the present invention to provide a combined cycle power plant that can further improve the efficiency of cooling the gas turbine system of the plant and that of collecting waste heat in the plant.

[0027] According to the present invention there is provided a combined cycle power plant comprising:

a gas turbine system having a gas turbine;
a waste heat collector boiler for collecting the waste heat of the exhaust of the gas turbine;
a steam cycle system having a steam turbine to be driven by the steam generated by the waste heat collector boiler; and
a gas turbine cooling system for feeding part or all of the steam and/or water generated in said steam cycle system into said gas turbine system and returning them into said steam cycle system, characterized in that:

said gas turbine cooling system is provided with

a cooling duct formed in two or more than two elements of said gas turbine system to be cooled and said steam and/or water is made to flow through said two or more than two elements; and

said combined cycle power plant further comprises a switching means for selectively supplying said steam and/or water coming from said steam cycle system or the high pressure air coming from said gas turbine system.

[0028] According to the present invention, the elements of the gas turbine are effectively cooled by the steam coming from the steam cycle system to allow gas with an ever higher temperature to be fed to the gas turbine system to improve the thermal efficiency of the gas turbine system.

[0029] According to the present invention, the efficiency of collecting waste heat from the gas turbine system is improved by the steam flowing through the turbine cooling system to consequently enhance the overall thermal efficiency of the plant.

[0030] The present invention is realized as a result of careful studies on the cooling system involving the use of steam and the system of collecting waste heat in existing combined cycle power plants of the type under consideration. According to the studies and analysis of the inventors of the present invention, the steam collected after cooling the blades of the gas turbine of any known combined cycle power plant shows a temperature rise of 50 to 200°C at most, evidencing that the cooling potential of the steam is exploited only partly.

[0031] Therefore, the efficiency of cooling the gas turbine can be improved to allow the use of higher temperature gas by effectively exploiting the cooling potential of the steam coming from the steam cycle system of any known combined cycle power plant. Then, the efficiency of collecting waste heat from the gas turbine system is accordingly improved to enhance the overall thermal efficiency of the plant.

[0032] As discussed above, according to the present invention, the cooling potential and the waste heat collecting potential of the steam coming from the steam cycle system of a combined cycle power plant can be effectively exploited by causing the steam to circulate through two or more than two elements of the gas turbine system such as the turbine blades and the combustor. According to a series of experiments conducted by the inventors of the present invention, the cooling potential and the waste heat collecting potential of the steam coming from the steam cycle system cannot be fully exploited if the steam is caused to flow through a single element of the gas turbine system such as the turbine blades of a single row.

[0033] More specifically, according to the present invention, steam is made to flow through a plurality of elements of the gas turbine system such as the turbine blades of a plurality of rows or the turbine blades of a

single row and the combustor to fully exploit the cooling potential and the waste heat collecting potential of the steam coming from the steam cycle system and improve the entire thermal efficiency of the combined cycle power plant.

[0034] The turbine cooling system through which steam flows typically comprises a cooling duct connecting a plurality of elements to be cooled either in series or in parallel. If it comprises a cooling duct connecting a plurality of elements to be cooled in parallel, steam flows through each of the element at a reduced flow rate to fully exploit the cooling potential and the waste heat collecting potential of the steam coming from the steam cycle system.

[0035] According to another characteristic feature of the present invention, there is provided a dust removing apparatus for cleansing the steam extracted from the steam cycle system of a combined cycle power plant to prevent scaly debris from being deposited on the inner surface of the cooling duct running through the turbine blades of the gas turbine and the combustor and hence any possible reduction in the efficiency of exploiting the cooling potential and the waste heat collecting potential of the steam coming from the steam cycle system. Additionally, since scaly debris are prevented from depositing on the surface of the cooling duct, the latter is not subjected to design limitations in terms of profile and cross section and hence a cooling duct having a high cooling effect can be designed for the purpose of the invention.

[0036] This invention can be more fully understood from the following detailed description when taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a schematic block diagram of a known combined cycle power plant.

FIG. 2 is a schematic block diagram of a first embodiment of combined cycle power plant according to the invention.

FIG. 3 is a schematic block diagram of a dust removing apparatus that can be used for the first embodiment of combined cycle power plant according to the invention.

FIG. 4 is a schematic block diagram of another dust removing apparatus that can be used for the first embodiment of combined cycle power plant according to the invention.

FIG. 5 is a graph illustrating the I-S relationship of steam that can be used for the purpose of the present invention.

FIG. 6 is a graph illustrating the relationship between the combined system efficiency and the gas turbine inlet temperature of the first embodiment of combined cycle power plant according to the invention.

FIG. 7 is a schematic block diagram of a third embodiment of combined cycle power plant according to the invention.

FIG. 8 is a schematic block diagram of a fourth embodiment of combined cycle power plant according to the invention.

FIG. 9 is a schematic block diagram of a fifth embodiment of combined cycle power plant according to the invention.

FIG. 10 is a schematic block diagram of a sixth embodiment of combined cycle power plant according to the invention.

FIG. 11 is a schematic block diagram of a seventh embodiment of combined cycle power plant according to the invention.

FIG. 12 is a schematic block diagram of an eighth embodiment of combined cycle power plant according to the invention.

FIG. 13 is a schematic block diagram of a ninth embodiment of combined cycle power plant according to the invention.

FIG. 14 is a schematic block diagram of a tenth embodiment of combined cycle power plant according to the invention.

FIG. 15 is a schematic block diagram of an eleventh embodiment of combined cycle power plant according to the invention.

FIG. 16 is a schematic block diagram of a twelfth embodiment of combined cycle power plant according to the invention.

FIG. 17 is a schematic block diagram of a thirteenth embodiment of combined cycle power plant according to the invention.

Firstly, a first embodiment of combined cycle power plant according to the invention will be described by referring to FIGS. 2 through 6 of the accompanying drawings.

[0037] The embodiment of combined cycle power plant comprises a gas turbine system 41, a steam cycle system 42 having a steam turbine driven by the exhaust energy of the gas turbine system 41 and a gas turbine cooling system 43 for cooling the blades and a peripheral area of the combustor of the gas turbine by means of part of the steam of the steam cycle system 42.

[0038] The gas turbine system 41 includes a gas turbine 111, a compressor 113 coupled with the gas turbine 111 by way of a shaft 112 and a combustor 114 that receives compressed air and fuel from the compressor 113 and burns the fuel to produce hot high pressure gas for driving the gas turbine 111.

[0039] The compressor 113 compresses the ambient air fed in through an air duct 115 and the compressed air is led to the combustor 114. The combustor 114 burns the fuel fed from a fuel supply system (not shown), using the compressed air as combustion sustaining gas. The hot gas obtained by combustion is then fed to the gas turbine 111 by way of a combustion gas duct 116 and allowed to inflate to drive the gas turbine 111 before flowing out through an exhaust gas duct 117.

[0040] On the other hand, the steam cycle system 42

comprises a steam turbine 118 and an electric generator 120 coupled with the steam turbine 118 by means of a shaft 119. A steam cycle is established in the steam cycle system as it generates steam by the waste heat of the gas turbine system 41 and the generated steam is used to drive the steam turbine 118. Note that the rotor of the steam turbine 118 and that of the gas turbine 111 are linked by a shaft 122 in FIG. 2.

[0041] The steam cycle system 42 is additionally provided with a waste heat collector boiler 123 for collecting heat from the exhaust gas of the gas turbine 111 fed through the exhaust gas duct 117 and generating hot high pressure steam necessary for driving the steam turbine 118. The exhaust gas from the waste heat collector boiler 123 is then emitted into the atmosphere by way of a flue 127. A high pressure superheater 125, a second high pressure evaporator 126, a first high pressure evaporator 127 and a high pressure preheater 128 are arranged in the waste heat collector boiler 123 in the above mentioned order from the upstream side toward the downstream side thereof. These heaters and the steam turbine 118 are connected with each other in a manner as described below to establish a steam cycle 42.

[0042] The steam expelled from the steam turbine 118 is led to a steam condenser 130 by way of an expelled steam duct 129 and reduced to water at room temperature. The collected room temperature water is led to the high pressure preheater 128 by way of a circulation pump 131 and a circulation conduit 132 for preliminary heating and then to a high pressure drum 134 by way of a conduit 133 leading to the drum. The pressurized water in the high pressure drum 134 is led to the first high pressure evaporator 127 by way of another circulation pump 135 for evaporation and the produced hot high pressure steam is returned to an upper space of the high pressure drum 134 by way of a return duct 136. The returned steam is then fed to the high pressure superheater 125 by way of a steam duct 137, a flow junction 138 and a steam duct 139 for reheating and the heated steam is further fed to the steam turbine 118 by way of a steam supply duct 140.

[0043] On the other hand, the gas turbine cooling system 43 has the following configuration.

[0044] Part of the pressurized water in the high pressure 134 is fed to the second high pressure evaporator 126 by way of a pressurized water supply pump 141 and pressurized water supply conduits 142, 145 for evaporation and the produced hot high pressure steam is then fed by way of a steam duct 146 to two elements to be cooled of the gas turbine system that are connected in series, namely the cooling duct 150 formed in the blades 149 and a cooling section 160 arranged in a peripheral area of the combustor 114. Then, after passing the two elements to be cooled, the steam is made to flow through a steam duct 151 and put together with the steam coming from the high pressure drum 134 at the flow junction 138. Although not shown in FIGS. 2

through 6, the steam piping of the embodiment may be provided with one or more than one flow rate control valves, one or more than one bypass valves and one or more than one steam check valves.

[0045] After passing through the elements to be cooled, as described above, the steam is made to flow through a steam duct 151 and put together with the steam coming from the high pressure drum 134 at the flow junction 138.

[0046] There is also provided a cooling steam duct 161, through which the high pressure air generated by the compressor 113 of the gas turbine system 41 may be fed to a dust removing apparatus 170 as regenerating air by way of an air duct 163 and an air valve 168.

[0047] The high pressure air passing through the dust removing apparatus 170 can be fed to an exhaust gas duct 117 by way of a exhaust duct 164, an air valve 166 and a gas turbine exhaust duct A.

[0048] While not shown in FIGS. 2 through 6, the steam piping of the embodiment may be provided with one or more than one flow rate control valves, one or more than one bypass valves and one or more than one steam check valves.

[0049] With the above arrangement, the dust and debris contained in the steam being fed by way of the steam duct 146 can be trapped, at least partly, before the steam passes through the elements to be cooled and the steam duct can be blocked by the steam valves 165 and 167.

[0050] Additionally, the scaly debris and dust adhering to the dust removing apparatus 170 can be removed to regenerate the apparatus by causing the high pressure air from the compressor 113 to flow through the dust removing apparatus 170 by way of the air valves 166 and 168 in the direction opposite to that of the flow of steam.

[0051] FIG. 3 is a schematic block diagram of the dust removing apparatus 170 of FIG. 2. The steam duct 146 is provided near the downstream end thereof with a steam switching device 270 comprised of a valve mechanism and then divided into two branch ducts 146a and 146b provided with respective dust removing units 170a and 170b. A third branch duct 146c that is not provided with a dust removing unit is also arranged between the above two branch ducts.

[0052] The dust removing units 170 and 170b are provided at the upstream and downstream sides thereof respectively with steam valves 173a and 173b and 167a and 167b before the two branch ducts are put together by way of respective steam ducts 161a and 161b at a flow junction 171, from which steam is further fed to a steam cooling section.

[0053] On the other hand, a collection system 200 is added to the dust removing apparatus for regenerating the latter. The collection system 200 is comprised of high pressure air feed-in ducts 163a and 163b connected respectively to the upstream sides of the valves 167a and 167b of the steam ducts 161a and 161b arranged down-

stream relative to the respective dust removing units 170a and 170b and provided with respective valves 168a and 168b for receiving air from a high pressure air source B and treated air discharge ducts 164a and 164b connected respectively to the downstream sides of the valves 173a and 173b of the steam ducts 146a and 146b arranged upstream relative to the respective dust removing units 170a and 170b and provided with respective valves 172a and 172b for discharging air to an exhaust treatment apparatus C.

[0054] The valves 167a, 167b, 168a, 168b, 172a, 172b, 173a and 173b, of the steam ducts 146a, 146b, 161a and 161b, the high pressure air feed-in ducts 163a and 163b and the treated air discharge ducts 164a and 164b can be manually operated to selectively open or close any of them.

[0055] In the collecting system 200 having the above described configuration, either one of the dust removing units 170a and 170b is made to allow steam to flow therethrough as the cooling medium of the gas turbine cooling system 43 by means of the steam switching device 270 when the plant is in operation. If, for example, the right side dust removing unit in FIG. 3, or the unit 170b, is operated, the valves 173b and 167b of the steam ducts 146b and 163b of the dust removing unit 170b are opened whereas the valves 168b and 172b of the high pressure air feed-in duct 163b and the treated air discharge duct 164b are closed.

[0056] Then, the right side dust removing unit in FIG. 3, or the unit 170b, allows steam to flow therethrough to remove dust from the steam operating for cooling the gas turbine.

[0057] On the other hand, in the left side dust removing unit in FIG. 3, or the unit 170a, whose operation is suspended, the valves 173a and 167a of the steam ducts 146a and 161a are closed whereas the valves 168a and 172b of the high pressure air feed-in duct 163a and the treated air discharge duct 164a are opened.

[0058] Then, the left side dust removing unit, or the unit 170a, causes high pressure air to flow in the direction opposite to that of air flow for dust removing operation in order to remove the dust trapped in the dust removing unit 170a and regenerate the latter.

[0059] When the operating dust removing unit 170b gets to a stage where it needs cleansing, the switching device 270 is operated to change the course of flowing steam and the valves are reversely operated to switch the operation of removing dust in the steam and that of regenerating the dust removing apparatus between the dust removing units 170a and 170b.

[0060] With the above arrangement, the dust removing units 170a and 170b are operated respectively for dust removal and for regeneration or vice versa on a constant basis so long as the turbine cooling system is held in operation.

[0061] The steam duct 146c having a switch valve 169 is arranged to bypass the dust removing apparatus when the components of the turbine cooling system is

serviced or in an emergency case. Thus, steam may be made to flow through the steam duct 146c whenever necessary.

[0062] While the air supply source of the above embodiment is the compressor 113 of the gas turbine system 41, air may alternatively be supplied from any source other than the compressor 113. The means for regenerating the dust removing apparatus is not limited to compressed air and any other material such as chemical solvent may alternatively be used for the purpose of the invention. The flow route of the regenerating means is not limited to the above description and any other appropriate route may be arranged for the purpose of the invention.

[0063] The steam guided through the duct 146 is made to flow through the cooling duct 150 of the blades 149 and the cooling section 160 in a peripheral area of the combustor 114 of the gas turbine connected in series and constituting two elements to be cooled in order to cool them. All or part of the steam used for the cooling operation is collected by the duct 151 and hence the collected steam is never mixed with the main stream gas to lower the temperature of the latter so that any unduly but necessary increase of the rate of feeding fuel and air to the combustor 114 can be prevented to increase the thermal efficiency of the plant.

[0064] Since two elements of the gas turbine system are serially cooled, the cooling potential of steam can be maximally exploited. Additionally, since the liner and the tail cylinder of the combustor 114 are also cooled by steam, any unduly but necessary increase in the air supply can also be prevented. Still additionally, since the blades of the gas turbine is constructed so as to be mostly cooled by conventional air, the gas turbine system is adapted to low quality fuel.

[0065] Furthermore, the specific output of the above embodiment can be remarkably raised. Still additionally, the cooling steam can be partly injected into the combustor as means for reducing the rate of NOx generation in the combustor 114 and/or discharged from the surface of the turbine blades for film cooling.

[0066] The steam passing through the gas turbine cooling system 43 of the above embodiment is then brought to the junction 138 by way of the steam duct 151 and put together with the steam coming from the high pressure drum 134 in the heating region of the steam cycle system 42. Then, the steam from the junction is heated again by the high pressure superheater 125 before fed to the steam turbine 118 so that the flow rate, the pressure and the temperature of the steam passing through the inlet of the steam turbine 118 can be made to get to the respective target values without being undesirably influenced by the gas turbine cooling system 43 and hence the steam turbine system can be operated with a maximum thermal efficiency.

[0067] Since cooling steam is made to flow from the gas turbine to the steam turbine in any known combined cycle power plant, the operation of the steam turbine can

become unstable when the load of the steam turbine and the steam temperature fluctuate. However, to the contrary, the above embodiment is free from such a problem and, since the steam is returned to the drum, the embodiment can be operated with a partial load by appropriately selecting the level of the pressure to be applied to the drum.

[0068] FIG. 6 is a graph showing the overall efficiency of the above embodiment of combined cycle power plant according to the invention and that of a known combined cycle power plant in comparison. The embodiment of combined cycle power plant according to the invention illustrated in FIG. 2 can improve the thermal efficiency of the steam turbine system to remarkably improve the overall thermal efficiency of the plant particularly in a high temperature region for the gas turbine inlet.

[0069] In the above embodiment, additionally, a dust removing apparatus 170 is arranged upstream relative to the gas turbine blades and other gas turbine components to be cooled by steam and designed to cleanse the upstream steam so that the advantages of the steam cooling method are not damaged and a desired cooling effect can be achieved at any time of operation throughout the service life of the combined cycle power plant.

[0070] Adhesion of scaly debris to the components of the turbine cooling system can be minimized by superheating the steam to be used for cooling operation by more than 10°C. Referring to FIG. 5 that illustrates the i-S relationship of steam, it is known that steam normally contains chemical substances to a slight extent and the saturation curve of any actual steam is slightly shifted to the high temperature side from that of pure steam. If the i-S curve crosses the saturation curve, steam is preferably used for cooling at temperature above the actual saturation curve illustrated by a dotted broken line because adhesion of scaly debris becomes remarkable in the wet area of the graph. The effect of preventing adhesion of scaly debris can be achieved by superheating the steam to be used for cooling operation by more than 10°C.

[0071] FIG. 4 is a schematic block diagram of another dust removing apparatus that can be used for the first embodiment of combined cycle power plant according to the invention. This apparatus differs from that of FIG. 3 in that the collecting system 200 is automatically switched. The components of the apparatus of FIG. 4 that are same as or similar to those of FIG. 3 are denoted respectively by the same reference symbols and only the differences of the two apparatus will be described hereinafter.

[0072] The dust removing apparatus of FIG. 4 is provided with arithmetic control units 175a and 175b for controlling the valves 173a, 173b, 167a and 167b of the steam ducts and differential pressure transducers 174a and 174b for respectively detecting the pressure differences between the upstream and the downstream of the dust removing units 170a and 170b.

[0073] The signals generated by the differential pres-

sure transducers 174a and 174b are read respectively by the arithmetic control units 175a and 175b so that the regenerating operation and the dust removing operation are automatically switched when the pressure difference between the upstream and the downstream of the dust removing units 170a or 170b, whichever appropriate, exceeds a predetermined level.

[0074] With the above arrangement, the combined cycle power plant is stable operated as the dust removing units 170a and 170b are automatically switched for dust removal and regeneration.

[0075] The above arrangement is also helpful when the turbines are started, stopped or operated with a partial load and a satisfactory supply of cooling steam is hardly achievable because part of the regenerating air can be used as cooling air and the water adhering to the steam ducts can be purged by air when the turbines are started or stopped.

[0076] Additionally, steam can be replaced by air or vice versa by operating the valves arranged on the steam ducts.

[0077] While two arithmetic control units 175a and 175b are used for controlling the valves in FIG. 4, the number of arithmetic control units to be used for the dust removing apparatus of a combined cycle power plant according to the invention may be varied depending on the number of dust removing units and other control units involved in the operation of the plant.

[0078] Thus, with the above arrangement, the gas turbine can be cooled effectively and scaly debris contained in the circulating steam can be effectively removed under various circumstances of the plant including the situation where the turbines are started, stopped or operated under a partial load to say nothing of normal operation periods. Additionally, the dust removing apparatus can be optimally regenerated.

[0079] Although not shown, the gas turbine cooling system may be provided with a switching device and so arranged that the cooling duct is separated from the steam cycle and made available for some other high pressure air supply source by operating the switching device or steam is supplied from some other steam engine to the gas turbine having elements to be cooled.

[0080] FIG. 7 is a schematic block diagram of a third embodiment of combined cycle power plant according to the invention. In this embodiment, steam is supplied from the high pressure evaporator 126 to the turbine blades 149 and the cooling section 160 of the combustor 114 in parallel and dust removing units 170c and 170d are arranged respectively corresponding to the turbine blades 149 and the cooling section of the combustor. The dust removing units 170c and 170d are designed to cool the cooling section 160 of the combustor and the turbine blades 149 respectively and separately. With such an arrangement, the dust removing units 170c and 170d can be provided with different meshes in correspondence to the respective objects to be cooled to maximize their dust removing effect for a prolonged pe-

riod of time.

[0081] FIG. 8 is a schematic block diagram of a fourth embodiment of combined cycle power plant according to the invention.

5 [0082] This embodiment differs from the embodiment of FIG. 2 in that a plurality of elements are cooled in the gas turbine cooling system 43a of this embodiment. More specifically, two rows of gas turbine blades 149 are provided with respective cooling ducts 150 and 158 and cooled by steam in the gas turbine cooling system 43a. Otherwise, this embodiment is identical with that of FIG. 2 and, therefore, the components of this embodiment that are same as or similar to those of FIG. 2 are denoted respectively by the same reference symbols and will not be described any further.

15 [0083] This embodiment is as effective as the first embodiment of FIG. 2 and additionally it can be adapted to multi-row gas turbines expected to appear in combined cycle power plants of the next generation.

20 [0084] FIG. 9 is a schematic block diagram of a fifth embodiment of combined cycle power plant according to the invention.

25 [0085] This embodiment is realized by slightly modifying the embodiment of FIG. 8 and differs from the latter in that two different elements are cooled by the gas turbine cooling system 43a. More specifically, in the gas turbine cooling system 43b of this embodiment, the portion of the duct located between a flow rate control valve 148 and the cooling duct 150 can be connected to the outlet of the compressor 113 by way of another flow rate control valve 153 and the portion of the duct located between the bypass valve 152 and the valve 154 can be connected to the exhaust gas duct 117 by way of a valve 155 and also to the steam condenser 130 by way of a valve 156 and a discharge duct 157. Otherwise, this embodiment is identical with that of FIG. 2 and, therefore, the components of this embodiment that are same as or similar to those of FIG. 2 are denoted respectively by the same reference symbols and will not be described any further.

30 [0086] This embodiment is as effective as the fourth embodiment of FIG. 8. In addition, it is helpful when the turbines are started, stopped or operated with a partial load and a satisfactory supply of cooling steam is hardly achievable from the second high pressure evaporator 126 because part of the air discharged from the compressor 113 can be made to flow through the cooling ducts 150 and 158 as cooling air to cool the blades 149 and the water adhering to the steam ducts can be purged by air when the turbines are started or stopped.

35 [0087] More specifically, part of the high pressure air discharged from the compressor 113 can be made to flow through the flow rate control valve 153, the cooling ducts 150 and 158, the exhaust gas duct 117 and the exhaust duct 157 by "closing" the flow rate control valve 148, the bypass valve 152 and the valve 154 and "opening" the flow rate control valve 153 and the valves 155 and 156 so that the steam path can be isolated to cool

the proper steam cooling section and purge the water lingering in the steam ducts. Additionally, steam can be replaced by air or vice versa by appropriately operating the valves in the steam ducts.

[0088] Thus, with the above described fifth embodiment, the gas turbine 111 can be effectively cooled by steam under various circumstances of the plant including the situation where the turbines are started, stopped or operated under a partial load to say nothing of normal operation periods. Although not shown, the gas turbine cooling system of the fifth embodiment may be provided with a switching device and so arranged that the cooling duct is separated from the steam cycle and made available for some other high pressure air supply source by operating the switching device or steam is supplied from some other steam engine to the gas turbine having elements to be cooled. Such an arrangement is as effective as any other arrangements described earlier.

[0089] FIG. 10 is a schematic block diagram of a sixth embodiment of combined cycle power plant according to the invention.

[0090] The sixth embodiment differs from the embodiment of FIG. 2 in terms of the configuration of the steam cycle system 121c. More specifically, in the steam turbine system 42c of this embodiment, the steam collected by way of the gas turbine cooling system 43 is then fed from the high pressure superheater 125 to another junction 138c on the way to the steam turbine 118 through the steam supply duct 140, which junction 138c is located at the end of the steam heating process. Otherwise, this embodiment is identical with that of FIG. 2 and, therefore, the components of this embodiment that are same as or similar to those of FIG. 2 are denoted respectively by the same reference symbols and will not be described any further.

[0091] With this arrangement again, the steam used to cool a plurality of elements of the gas turbine 111 is subjected to a sufficient heat exchanging operation and therefore does not need to go through the high pressure superheater 125 in the waste heat collector boiler 123 so that the combined cycle power plant can be made more compact with an improved overall thermal efficiency.

[0092] FIG. 11 is a schematic block diagram of a seventh embodiment of combined cycle power plant according to the invention.

[0093] In this embodiment, all the steam generated by the high pressure drum 33 is made to pass through the duct 37, the cooling duct 150 of the gas turbine blades 149 to be cooled and the cooling duct 158 of the section 160 to be cooled by steam of a peripheral area of the combustor and of the gas turbine blades 149 to be cooled and, after cooling these elements, fed to the steam turbine 118 by way of the steam duct 151.

Otherwise, this embodiment is identical with that of FIG. 2 and, therefore, the components of this embodiment that are same as or similar to those of FIG. 2 are denoted respectively by the same reference symbols and will not

be described any further.

[0094] With this arrangement, the specific output of the above embodiment can be remarkably raised. Additionally, there is provided a steam injection device 170 by means of which the cooling steam can be partly injected into the combustor 14 as means for reducing the rate of NOx generation in the combustor 14 and/or discharged from the surface of the turbine blades for film cooling.

[0095] In this embodiment again, the steam used to cool a plurality of elements of the gas turbine 111 is subjected to a sufficient heat exchanging operation and therefore does not need to go through the high pressure superheater 25 in the waste heat collector boiler 23 so that the combined cycle power plant can be made more compact with an improved overall thermal efficiency.

[0096] While not shown, this seventh embodiment may be adapted to serial or parallel cooling of a plurality of elements of the gas turbine to be cooled by appropriately selecting the mode of supplying cooling steam.

[0097] FIG. 12 is a schematic block diagram of an eighth embodiment of combined cycle power plant according to the invention.

[0098] The embodiment of FIG. 12 is realized by combining the known plant of FIG. 1 and a plant according to the invention in an appropriate way.

[0099] More specifically, the pressurized water in the high pressure drum 33 is fed through the circulation pump 34 and the pressurized water conduit 142 to cool the cooling duct 150 formed in the gas turbine blades 149, one of the two serially connected elements to be cooled, and then the cooling section 160 in a peripheral area of the combustor 114, the other of the two elements.

[0100] After passing through the two elements to be cooled, the pressurized and heated water is fed to the high pressure evaporator 25.

[0101] This arrangement is particularly effective when a plurality of elements of the gas turbine are cooled by pressurized water.

[0102] FIG. 13 is a schematic block diagram of a ninth embodiment of combined cycle power plant according to the invention.

[0103] In this embodiment, the cooling ducts 150 and 158 and the collection duct 151 are led to the high pressure drum 134 so that the pressurized water passing through the duct 151 may partly be evaporated to produce liquid having both a gas phase and a liquid phase there. The effect of this embodiment may be enhanced when the collection conduit 151 is led to an upper portion of the high pressure drum 134.

[0104] Then, the fluid with a gas phase and a liquid phase is then divided into water and steam in the high pressure drum 134.

[0105] The fluid flowing through the collection duct 151 may alternatively have a single phase of gas or liquid.

[0106] FIG. 14 is a schematic block diagram of a tenth

embodiment of combined cycle power plant according to the invention and comprising a gas turbine system having a plurality of gas turbines.

[0107] In this embodiment of combined cycle power plant, the steam generated in an existing conventional gas turbine plant 201 and a waste heat collector boiler 221 utilizing the waste heat of the gas turbine plant 201 is fed in parallel to independent gas turbine systems 301, 401 and 501 provided with respective steam cooling systems in order to cool the gas turbines. After passing through the cooling systems, the steam is fed to an aggregative steam conduit 229 by way of respective collector conduits 306, 406 and 506 and supplied to the steam turbine 218 to drive the latter.

[0108] After passing through the steam turbine 218, the steam is turned back to room temperature water by a steam condenser 224 and the produced room temperature water is fed to a steam generator 222 of the waste heat collector boiler 221 by means of a circulation pump 225 to establish a first closed loop.

[0109] On the other hand, the gas turbine systems 301, 401 and 501 are provided with respective waste heat collector boilers 309, 409 and 509 for utilizing the waste heat of the systems 301, 401 and 501 and the steam generated by the steam generating sections 308, 408 and 508 of the waste heat collector boilers 309, 409 and 509 is fed to an aggregative steam conduit 230 by way of respective steam collector conduits 311, 411 and 511 and then supplied to a large independent steam turbine 231 to drive the latter.

[0110] After passing through the large steam turbine 231, the steam is fed to a steam condenser 233 by way of a conduit 232 and turned back to room temperature water by the steam condenser 233 and the produced room temperature water is fed to the steam generating sections 308, 408 and 508 of the waste heat collector heater 309, 409 and 509 by means of a circulation pump 235 to establish a second closed loop.

[0111] Note that the compressors 213, 302, 402 and 502, the combustor 214, 304, 403 and 503, the duct 215, the gas turbines 211, 304, 404 and 504, the rotary shafts 212 and 219, the electric generators 220, 305, 405, 505 and 605 are same as or similar to their counterparts of the known plant of FIG. 1 and the embodiment of FIG. 2 and therefore will not be described any further.

[0112] With this arrangement, the steam generated by the existing conventional combined cycle power plant can be fed to the steam cooling sections of the newly constructed gas turbines 304, 404 and 504 and the cooling steam expelled from the gas turbines can be collected by means of the steam cycle of the combined generating system.

[0113] On the other hand, the steam generated by the waste heat collector boilers 309, 409 and 509 utilizing the waste heat of the gas turbines 304, 404 and 504 is fed to the independent large steam turbine 231 to generate electricity with a remarkably enhanced efficiency so that the plant can operate with a maximal thermal

efficiency.

[0114] In short, this embodiment provides a maximal overall thermal efficiency if it is designed as a single combined cycle power plant or as a combination of a plurality of combined cycle power plants.

[0115] Additionally, the cooling potential of the cooling steam can be maximally exploited by arranging the gas turbine blades and other gas turbine components in series, in parallel or a combination thereof as the steam used for cooling a plurality of elements is returned to the steam cycle.

[0116] FIG. 15 is a schematic block diagram of an eleventh embodiment of combined cycle power plant according to the invention.

[0117] In this embodiment, the gas turbine blades 149 and a cooling section 160 arranged in a peripheral area of the combustor 114 are cooled in parallel by steam flowing through respective branches of the cooling steam supply duct 146 in the gas turbine cooling system 43a. Otherwise, this embodiment is identical with that of FIG. 2 and, therefore, the components of this embodiment that are same as or similar to those of FIG. 2 are denoted respectively by the same reference symbols and will not be described any further.

[0118] This arrangement is as effective as the first embodiment of FIG. 2. Additionally, the flow rate of the steam fed to the cooling section 160 in a peripheral area of the combustor 114 and that of the steam fed to the gas turbine blades 149 can be controlled independently to enhance the effect of cooling the different components of the gas turbine system.

[0119] FIG. 16 is a schematic block diagram of a twelfth embodiment of combined cycle power plant according to the invention.

[0120] This embodiment is obtained by modifying the embodiment of FIG. 10 in terms of the arrangement of the steam turbine system 42 and that of the waste heat collector boiler 123.

[0121] More specifically, in this embodiment, the steam turbine 118 is comprised of a high pressure steam turbine 118a and a low pressure steam turbine 118b and the steam from the high pressure heater 125 of the waste heat collector boiler 123 is fed to the high pressure steam turbine 118a by way of the steam supply duct 140. The steam inflated by the high pressure steam turbine 118a is then collected by steam duct A and returned to the waste heat collector boiler 123, where it is repeated and fed to the low pressure steam turbine 118b. The collected cooling steam coming from the gas turbine cooling system 43a is also fed to the inlet of the low pressure steam turbine 118b. Otherwise, this embodiment is identical with that of FIG. 2 and, therefore, the components of this embodiment that are same as or similar to those of FIG. 2 are denoted respectively by the same reference symbols and will not be described any further.

[0122] This arrangement is as effective as the embodiment of FIG. 10. Additionally, the overall thermal efficiency of the plant is further enhanced because of the

fact that the steam cycle of this embodiment constitutes a reheating cycle.

[0123] FIG. 17 is a schematic block diagram of a thirteenth embodiment of combined cycle power plant according to the invention.

[0124] This embodiment is obtained by modifying the twelfth embodiment of FIG. 16 in such a way that the steam inflated by the high pressure steam turbine 118a of the steam turbine 118 and collected from steam duct C is directly fed to the gas turbine cooling system 43 without passing through the waste heat collector boiler 123 in order to cool the gas turbine cooling system 43 and establish a steam reheating cycle. Otherwise, this embodiment is identical with that of FIG. 16 and, therefore, the components of this embodiment that are same as or similar to those of FIG. 16 are denoted respectively by the same reference symbols and will not be described any further.

[0125] This arrangement is as effective as the twelfth embodiment of FIG. 16. Additionally, the overall thermal efficiency of the plant is further enhanced at reduced cost because of the simplified configuration of the steam cycle system.

Claims

1. A combined cycle power plant comprising:

a gas turbine system (41) having a gas turbine (111, 211, 304, 404, 504);
a waste heat collector boiler (123, 221, 309, 409, 509) for collecting the waste heat of the exhaust of the gas turbine;
a steam cycle system (42) having a steam turbine (118, 218, 231) to be driven by the steam generated by the waste heat collector boiler; and
a gas turbine cooling system (43, 43a, 43b) for feeding part or all of the steam and/or water generated in said steam cycle system into said gas turbine system (41) and returning them into said steam cycle system, **characterized in that:**

said gas turbine cooling system (43, 43a, 43b) is provided with a cooling duct (150, 152, 160) formed in two or more than two elements (114, 149) of said gas turbine system (41) to be cooled and said steam and/or water is made to flow through said two or more than two elements; and
said combined cycle power plant further comprises a switching means (153) for selectively supplying said steam and/or water coming from said steam cycle system (42) or the high pressure air coming from said gas turbine system (41).

2. A combined cycle power plant according to claim 1, **characterized in that** it further comprises a bypass duct (157) in the path for returning part or all of the steam and/or water coming from the cooling duct (150, 152, 160) of said turbine cooling system (43, 43a, 43b), said bypass (157) communicating with the waste heat collector boiler (123) or a steam condenser (130) of the steam cycle system (42).

3. A combined cycle power plant according to claim 1, **characterized in that** said steam and/or water coming from said cooling duct (150, 152, 160) of said turbine cooling system (43, 43a, 43b) is fed to another steam cycle system or a heat supply source.

4. A combined cycle power plant according to claim 1, **characterized in that** said turbine cooling system (43, 43a, 43b) is fed with steam and/or water from another steam engine.

5. A combined cycle power plant according to claim 1, **characterized in that** part or all of said steam and/or water coming from said cooling duct (150, 152, 160) is returned to a location downstream to the steam heating process of said steam cycle system (42).

6. A combined cycle power plant according to claim 1, **characterized in that** said steam and/or water fed to said cooling duct (150, 152, 160) is supplied from the location of an inflating process of said steam cycle system (42).

7. A combined cycle power plant according to claim 1, **characterized in that** part or all of said steam and/or water coming from said cooling duct (150, 152, 160) is returned to the location of an inflating process of said steam cycle system (42).

8. A combined cycle power plant according to claim 1, **characterized in that** said elements (114, 149) to be cooled are the combustor (114) and the turbine blades (149) of the gas turbine system (41) and the steam and/or water fed from said steam cycle system (42) is supplied to the cooling duct (160) of said combustor (114) after passing through the cooling duct (150) in said turbine blades (149).

9. A combined cycle power plant according to claim 1, **characterized in that** said steam and/or water is returned to a steam drum (134) of said steam cycle system (42) after passing through the cooling duct (150, 152, 160) of said turbine cooling system (43, 43a, 43b).

10. A combined cycle power plant according to claim 1, **characterized in that** the steam and/or water fed

from said steam cycle system (42) to said turbine cooling system (43, 43a, 43b) is supplied from the high pressure drum (134) and/or the condenser (130) of the steam cycle system (42) and the steam and/or water returned from the turbine cooling system (43, 43a, 43b) to the steam cycle system (42) is specifically returned to at least one of the waste heat collector boiler (123), the steam drum (134) and the condenser (130) of the steam cycle system.

10

15

20

25

30


35

40

45

50

55






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8








FIG. 11






FIG. 13




FIG. 14




FIG. 15





FIG. 16





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 01 12 7006

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	PATENT ABSTRACTS OF JAPAN vol. 017, no. 530 (M-1485), 24 September 1993 (1993-09-24) & JP 05 141267 A (MITSUBISHI HEAVY IND LTD), 8 June 1993 (1993-06-08) * abstract *	1,5-7	F01K23/10 F02C7/16
Y	PATENT ABSTRACTS OF JAPAN vol. 018, no. 360 (M-1634), 7 July 1994 (1994-07-07) & JP 06 093879 A (HITACHI LTD), 5 April 1994 (1994-04-05) * abstract *	1,5-7	
A	US 4 571 935 A (RICE IVAN G) 25 February 1986 (1986-02-25) * column 10, last paragraph - column 11, paragraph 1; figure 1 *	1,5-7	
A	PATENT ABSTRACTS OF JAPAN vol. 016, no. 434 (M-1308), 10 September 1992 (1992-09-10) & JP 04 148035 A (TOSHIBA CORP), 21 May 1992 (1992-05-21) * abstract *	1	TECHNICAL FIELDS SEARCHED (Int.Cl.7) F01K F02C
A	US 5 412 937 A (TOMLINSON LEROY O ET AL) 9 May 1995 (1995-05-09) * column 3, line 24 - line 37; figures *	1,2	
E	EP 0 743 425 A (GEN ELECTRIC) 20 November 1996 (1996-11-20) * column 6, line 2 - line 18 * * column 7, line 17 - line 43; figures * -/--	1,2,5-7	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 4 January 2002	Examiner Van Gheel, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/82 (P0401)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 12 7006

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A,P	EP 0 674 099 A (ABB MANAGEMENT AG) 27 September 1995 (1995-09-27) * page 3, line 30 - page 4, line 36; figures * -----	1,5-8	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 4 January 2002	Examiner Van Gheel, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1500 (03/92) (1/94C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 12 7006

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-01-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 05141267	A	08-06-1993	JP 2984442 B2	29-11-1999
JP 06093879	A	05-04-1994	NONE	
US 4571935	A	25-02-1986	US 4314442 A	09-02-1982
			US 4272953 A	16-06-1981
			CA 1160463 A1	17-01-1984
			CA 1170842 A2	17-07-1984
			DE 2967660 D1	09-07-1987
			EP 0020594 A1	07-01-1981
			JP 55500847 T	23-10-1980
			WO 8000864 A1	01-05-1980
			US 4896499 A	30-01-1990
			US 4384452 A	24-05-1983
			JP 63147931 A	20-06-1988
			US 4835958 A	06-06-1989
			US 4438625 A	27-03-1984
			US 4507914 A	02-04-1985
			US 4545197 A	08-10-1985
			US 4592204 A	03-06-1986
			US 4813227 A	21-03-1989
			US 4638628 A	27-01-1987
JP 04148035	A	21-05-1992	NONE	
US 5412937	A	09-05-1995	US 5428950 A	04-07-1995
			US RE36497 E	18-01-2000
			US RE36524 E	25-01-2000
			US 5628179 A	13-05-1997
			US 5577377 A	26-11-1996
EP 0743425	A	20-11-1996	US 5577377 A	26-11-1996
			EP 0743425 A1	20-11-1996
			JP 9112292 A	28-04-1997
			US RE36497 E	18-01-2000
EP 0674099	A	27-09-1995	DE 4409567 A1	28-09-1995
			CN 1112985 A ,B	06-12-1995
			EP 0674099 A1	27-09-1995
			JP 7259510 A	09-10-1995
			US 5613356 A	25-03-1997

EPO FORM P0458

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82